

CE

COBRA NON-LUBE ROOFBOLTER

Quality System
 Quality
 Endorsed
 Company
 ISO 9001:2000
 Lic No. QEC 21300
 Standards Australia

The Cobra Non-Lube Roofbolter has been developed by Rambor Pty Ltd to bring the hand held roofbolting method into the 21st century

The new non-lube Roofbolter will:

- Improved OH&S by eliminating oil vapors in exhaust air
- Eliminate in-line Lubrication
- Reduce maintenance
- Reduce wear & tear
- Eliminate hydraulic locking of control and dump valves
- Reduced likelihood of icing of muffler

The Motor, Gearbox and Muffler is all housed in a plastic casing which makes it much lighter than SGI

The non-lube can also be purchased with a wet, dry or dust collection drive unit

It comes fitted with standard, 4 stage or maxi legs and a t/bar handle



Also available with a pistol grip handle



PH: 61 2 4422 6323

FAX: 61 2 4422 5423

www.rambor.com.au



Manufactured by:
RAMBOR PTY LTD
 ABN 61 105 301 184
 108 ALBATROSS ROAD
 SOUTH NOWRA
 NSW AUSTRALIA 2541



Technical Specifications for :COBRA NON-LUBE ROOFBOLTER

Motor 95mm High Torque Gearbox

Normal Running	100 - 120 cfm	2832 - 3398 l/m
At Stall	50 - 60 cfm	1416 - 1557 l/m
Stall Torque	180 ft/lb	244 Nm
Rotation 600 - 700 rpm (no load)	100 - 120 cfm	2832 - 3398 l/m

Std Machine Thrust

1st Stage	2000 lbf	907 kgf
2nd Stage	1500 lbf	680 kgf
3rd Stage	1000 lbf	453 kgf

Maxi Machine Thrust

1st Stage	2500 lbf	1134 kgf
2nd Stage	2000 lbf	907 kgf
3rd Stage	1500 lbf	680 kgf

Torque

Torque	185 ft/lb	250 Nm
Noise level	84-95 dB(A)	84 - 95 dB(A)
Weight range	33.5 - 44.5 kg	33.5 - 44.5kg

REFER TO RAMBOR® ROOFBOLTER OPERATORS GUIDE AND SAFETY POINTS FOR SAFE WORKING PRACTICES