

CE

DOUBLE REDUCTION GENERAL PURPOSE MOTOR

Certified System
Quality
ISO 9001
SAI GLOBAL



- Designed to achieve high torque with a small motor and low air consumption
- Portable unit
- Motor separates from Reduction Box for easy maintenance
- Infinitely variable speed from 0-375 rpm

- Comes with standard SAE 2 bolt flange which can replace a standard Hydraulic Motor
- Shaft has an M30 thread. Also available with 19 hex, 22 hex or 1" square drive chucks
- Suitable for Conveyors, Grout & Resin Mixers, Pumps and Winches



PH: 61 2 4422 6323 FAX: 61 2 4422 5423 www.rambor.com.au

Manufactured by:
RAMBOR PTY LTD
ABN 61 105 301 184
108 ALBATROSS ROAD
SOUTH NOWRA
NSW AUSTRALIA 2541

The unit can be purchased at different torque & speed outputs to suit applications

| Max Air Consumption 90 cfm (2.5 m ³) @ 100 psi (689 kpa) | | |
|--|----------|-------------------|
| Model | RPM | Stall Torque |
| 1590-0003 | 375 | 177 ft/lbs 240 Nm |
| 1590-0004 | 275 | 243 ft/lbs 330 Nm |
| 1590-0005 | 200 | 335 ft/lbs 454 Nm |
| Weight | 13.5 kg | |
| Noise Level | 86 dB(A) | |

Note: 19 hex chuck shaft has M30 thread

