

CE

H-BAR DRILL



Quality
ISO 9001
SAI GLOBAL



The H-Bar Drill is a High Torque Machine fitted with a 70mm or 95mm SGI Motor and Gear Box, which has a 14:39 ratio fitted with cone and cup bearings in the top end to withstand end loads when drilling

The configuration fitted with RAMBOR'S unique silencer system is far quieter than any other machine previously used. In fact noise levels registered as low as 84 dB(A) at coal face area. Higher rates up to 95 dB(A) would be obtained in workshop areas constructed of masonry or iron walls.

The design of the silencer ensures that oil misting on discharge is kept to an absolute minimum.

Special Features:

- Rugged construction 'H' design stainless steel Handle
- Easy trigger operations
- Pneumatic Drill
- Has through spindle coolant
- Safety Trigger Guard
- Operated by two men
- Chuck to suit applications
- Drills holes in floor of mines, concrete and earth construction



PH: 61 2 4422 6323

FAX: 61 2 4422 5423

www.rambor.com.au

Manufactured by:
RAMBOR PTY LTD
ABN 61 105 301 184
108 ALBATROSS ROAD
SOUTH NOWRA
NSW AUSTRALIA 2541



H-BAR Specifications @ 689 kPa [100 psi]

70 mm Motor with 14:39 ratio gearbox

Normal Running 850-900 rpm	2832 - 3256 l/m
Stall Torque	203 Nm
RPM (no load)	850-900
Water Supply	861-1206 kPa
Water flow rate	12-13 l/m
Noise Level	84 - 95 dB(A)
Weight	26 kg

H-BAR Specifications @ 689 kPa [100 psi]

95 mm Motor with 14:39 ratio gearbox

Normal Running 850-900 rpm	2832 - 3398 l/m
Stall Torque	251 Nm
RPM (no load)	850-900
Water Supply	861-1206 kPa
Water flow rate	12-13 l/m
Noise Level	84 - 95 dB(A)
Weight	26 kg