

CE

LOW SEAM DRILL 1200



Quality
ISO 9001

SAI GLOBAL

The Low Seam Drill is a free standing complete drilling system

The *Drill Carriage* design enables the longest drilling stroke possible in the roof height where it is operating

The Drill Carriage is powered by a double acting pneumatic cylinder, meaning carriage powers up and powers down

Using an *Air Cylinder* to operate the carriage, means less maintenance and less down time

The Low Seam Drill is controlled by *Remote Control* so the operator can stand clear of the machine. The Remote is a *Pistol* type design with levers operating extension, retraction and water

The Low Seam Drill has two stinger legs, allowing the Drill to be rotated through 360° The stingers are double acting, power up, power down, which means the stingers will not get stuck in the roof when trying to move to the next drilling position

A removable buggy makes the transport and movement easier

The Low Seam Drill is *Stainless Steel* construction and the cylinder rod of the 1st Inner Drill legs are stainless steel

Closed/collapsed height	1200 mm
Extended height	2000 mm
Drill Stroke	500 mm



- **A longer frame life with no rust problems**
- **Better, safer working method**
- **More productivity**
- **More comfort**
- **Working smarter not harder**
- **Stepping out of the dark ages**



PH: 61 2 4422 6323 FAX: 61 2 4422 5423 www.rambor.com.au



Manufactured by:
RAMBOR PTY LTD
ABN 61 105 301 184
108 ALBATROSS ROAD
SOUTH NOWRA
NSW AUSTRALIA 2541



TECHNICAL SPECIFICATIONS

With **95mm** MOTOR WITH 14-39 GEAR RATIO
 MOTOR SPECS AT 1000 lbf (453 kgf) THRUST

	@ 689 kpa 14-39 ratio	@ 413 kpa 14-39 ratio
R.P.M (no load)	850 - 900	600
Air Consumption	2832 - 3398 l/m	2832 - 3398 l/m
Water supply	992 litres/min	992 litres/min
Water supply pressure @ 7-12 Bar / 100 psi - 175 psi	700 - 1206 kPa	700 - 1206 kPa
Water flow rate hi flow @ 7 Bar / 100 psi	12-13 l/min	12-13 l/min
Stall torque	251 Nm	163 Nm
Noise level	84-95 dB(A)	84 - 95 dB(A)
<u>Thrust</u>		
Stinger Leg	1134 kgf per leg	680 kgf per leg
Drill Leg	907 kgf per leg	544 kgf per leg
Weight	128 kg	128 kg

Removable
Buggy



The Low Seam Drill 1200 has two stinger legs, allowing the drill to be rotated through 360°

REFER TO **RAMBOR®** ROOFBOLTER OPERATORS GUIDE AND SAFETY POINTS
 FOR SAFE WORKING PRACTICES